Appendix C List of Symbols

| A | Amplitude of a vibratory roller |
|----------------------------|--|
| e | Void ratio |
| c | Percent by weight of coarser fraction of the total material, expressed as a decimal, (1-f) |
| C | A dimensionless constant in calculating the centrifugal force of a vibratory roller = 35198 |
| CF_{1000} | Vibratory roller centrifugal force operating at 1000 vpm |
| CF_{1500} | Vibratory roller centrifugal force operating at 1500 vpm |
| f | Percent by weight of finer fraction of the total material, expressed as a decimal, (1-c) |
| k | Coefficient of permeability |
| g | Acceleration due to gravity |
| $G_{\scriptscriptstyle m}$ | Bulk specific gravity |
| G_s | Grain specific gravity or specific gravity of solids |
| Н | Diamond core drill size, nominal 7.6 cm (3 in.) |
| $H_{\scriptscriptstyle W}$ | Applied hydraulic head in the USBR constant-head permeability test |
| h_0 | Initial depth of water in the open-pit permeability test |
| h | Depth of water in open-pit permeability test at time $t = \Delta t$ |
| h_1 | Height of water above tip of the standpipe at time $t = t_1$ in the Schmid falling-head test |
| h_2 | Height of water above the tip of the standpipe at time $t=t_2$ in the Schmid falling-head test |
| n | porosity |
| n_r | porosity of the rock particle |
| N | Diamond core drill size, nominal 5.1 cm (2 in.) |
| Q | A rock classification system for engineering purposes |
| Q_d | Flow rate in a constant-head permeability test |
| RMR | A rock classification system for engineering purposes |
| RQD | Rock Quality Determinator |

EM 1110-2-2301 30 Sep 94

Inside radius of the standpipe in the standpipe permeability test r_0 S Degree of saturation Initial degree of saturation of the compacted fill S_{i} S_w Wetted degree of saturation of the compacted fill during the permeability test Vibrations per minute vpmWater content wThe unsprung weight of a vibratory roller drum module W_{u} Change in head over the time interval Δt in the falling-head permeability test Δh ΔS Change in degree of saturation from the as-compacted condition to a wetted condition Elapsed time in the falling-head permeability test Δt Dry density γ_d Dry density of the finer fraction γ_f Bulk density γ_m γ_t Dry density of the total material Unit weight of water γ_w λ Mean number of discontinuities per meter in a rock mass

π

The constant Pi = 3.1416